

PAPER • OPEN ACCESS

A New Technique for Solar Cell Parameters Estimation of The Single-Diode Model

To cite this article: Mohammed Rasheed *et al* 2021 *J. Phys.: Conf. Ser.* **1879** 032120

View the [article online](#) for updates and enhancements.

 <p>The Electrochemical Society Advancing solid state & electrochemical science & technology 2021 Virtual Education</p> <p>Fundamentals of Electrochemistry: Basic Theory and Kinetic Methods Instructed by: Dr. James Noël Sun, Sept 19 & Mon, Sept 20 at 12h–15h ET</p> <p>Register early and save!</p>	
--	--

A New Technique for Solar Cell Parameters Estimation of The Single-Diode Model

Mohammed RASHEED¹, Osama Alabdali², Suha Shihab¹

¹Applied Sciences Department, University of Technology, Baghdad, Iraq.

²College of Education for Pure Sciences, University of Anbar, Al-Anbar, Iraq.

E-mail: 10606@uotechnology.edu.iq

Abstract. In the current study, an implicit algorithm has been applied to solve the nonlinear equation of a single diode solar cell using several iterations with an initial value of $x_0 = 1$. The proposed algorithm is achieved with the different values of load resistance. The equation based on equivalent circuit of a solar cell and all the determinations are implemented at ambient temperature using MATLAB program. The obtained results of this new method are given, and the absolute errors are investigated.

Keywords: Implicit method; single diode model; parameters; iterations; load resistance.

1. Introduction

Numerical analysis is a science of approximation where numerical methods are used to solve complex and unsolvable problems by analytical methods. In numerical analysis, all aspects of the existing problem are studied numerically, using theoretical development, understanding of numerical methods, and attempting to implement them in the form of computer programs. These programs are characterized by a high level of confidence and effectiveness. Common interests and perspectives among them, which include mathematical methods of numerical analysis is based on the principle of creating, analyzing, and implementing a number of algorithms to arrive at digital solutions to mathematical problems that are built on a range of constant variations and fluctuations, such as quantitative analysis, or numerical methods [1-8]. Photovoltaic have been used in space for a long time in 1958, when Van Gard was launched, with 6 photovoltaic cells on its surface. While other batteries stopped working shortly after the ship was launched, since then, solar photovoltaic cells have been widely used in space and their use has helped to increase the length of spaceflight. For spaceships and high reliability relatively high yield. The main idea is to reproduction electrical energy by means of photovoltaic cells, which form solar cells. Several kinds of solar cells are synthesized based on the material used and fabrication technique such as silicon, organic and inorganic solar cells [9-55]. This study proposes a method for estimating parameters in single diode model of a solar cell equation based on implicit algorithm (IM) and explains the performance of this estimation method. It is organized as follows: Section two characterizing the analytical model of a single-diode design of the solar cell; Section three establishing the root finding Implicit algorithm (IM); Section four results and discussion; Section five conclusions of the acquired results.



2. Characteristics of Single-Diode Solar Cells Equation

A photo voltaic cell (equivalent circuit) is shown in Figure 1.




Figure 1. Single-diode electrical equivalent circuit model of a solar cell.

By applying Kiechoff's current law for the circuit, the equation of this equivalent circuit is given by

$$I = I_{ph} - I_D \quad (1)$$

$$I_D = I_0 \left(e^{\frac{-V_{pv}}{nV_T}} - 1 \right) \quad (2)$$

$$I = I_{ph} - I_0 \left(e^{\frac{-V_{pv}}{mV_T}} - 1 \right) \quad (3)$$

where:

I_{ph} is the photocurrent (A); I_0 is reverse saturation current of the diode (A); I and V_{pv} are the delivered current and voltage, respectively (V); $V_T = \frac{kT}{q} = 0.0259$ V is thermic voltage = $27.5 \cong 26$ mV at ($T = 25$ °C Air-Mass = 1.5); m is the recombination factor closeness to an ideal diode ($1 < m < 2$), k is Boltzmann constant = 1.38×10^{-23} J/K; T is $p - n$ junction temperature (K); q is the electron charge = 1.6×10^{-19} C.

$$I_{ph} = I_{source} \quad (4)$$

$$I_D = I_s * \left(e^{\frac{V_D}{nV_T}} - 1 \right) \quad (5)$$

Merge Eq. 4 in Eq. 5 we get

$$(I_{source}) - 10^{-12} \left(e^{\frac{-V}{1.2 * 0.026}} - 1 \right) = \frac{V}{R} \quad (6)$$

where: I_s reverse saturation current = 10^{-12} A. In parallel, $V_D = V_{pv} = V$

According to Eq. 6 one can calculate V of the cell numerically based on the first derivative of this equation.

3. Implicit Method (IM)

The following algorithm suggestion for solving Eq. 5 by using NRM

Initial approximate solution $x_0 = 1$, tolerance ϵ ,

$$\hat{f}(x_{n+1}) = x_n - \frac{f(x_n)}{f'(x_n)} \text{ for } n = 0, 1, 2, \dots$$

$$x_{n+1} = x_n - \frac{2 \times f(x_n)}{\hat{f}(x_{n+1}) + \hat{f}(x_n)}$$

In the implicit formula, the indefinite integral involved in the following equation

$$f(x) = f(x_n) + \int_{x_n}^x \hat{f}(\lambda) d\lambda \quad (7)$$

Is approximated by the trapezoidal rule to obtain

$$\int_{x_n}^x \hat{f}(\lambda) d\lambda = \frac{x-x_n}{2} [\hat{f}(x_n) + \hat{f}(x)] \quad (8)$$

Put Eq. 8 into Eq. 7 yields

$$f(x) = f(x_n) + \frac{x-x_n}{2} [\hat{f}(x_n) + \hat{f}(x)] \quad (9)$$

Since $f(x) = 0$, therefore Eq. 9 can be written as

$$x = x_n - \frac{2 \times f(x_n)}{[\hat{f}(x_n) + \hat{f}(x)]} \quad (10)$$

Take the next iterative point, that is put $x = x_{n+1}$ to obtain

$$f(x_{n+1}) = f(x_n) + \frac{1}{2}(x_{n+1} - x_n)(\hat{f}(x_n) + \hat{f}(x_{n+1})) \text{ or}$$

$$x_{n+1} = x_n - \frac{2 \times f(x_n)}{\hat{f}(x_{n+1}) + \hat{f}(x_n)} \quad (11)$$

Eq. 11 is an implicit formula, which requires having the derivative of the function at the $(n+1)^{th}$ iterative step to calculate the $(n+1)^{th}$ iterative itself.

Thus, the resulting formula is

$$x_{n+1} = x_n - \frac{2 \times f(x_n)}{\hat{f}(x_{n+1}^*) + \hat{f}(x_n)}$$

$$\text{where: } \hat{f}(x_{n+1}^*) = x_n - \frac{f(x_n)}{\hat{f}(x_n)}, \quad n = 0, 1, 2, \dots \quad (12)$$

and x_0 is the starting value

4. Results and Discussion

Consider Eq. 6 is modelled in the form single-diode solar cell has obtained the following approximate solutions and the IM are applied with the first initial value x_0 . In Table 1, the IM of the solution results (voltage V_{pv} ; current I_{pv} and power P_{pv} of the solar cell) are presented and listed in this table when the load resistance $R = 1$.

Table 1 and Figure 3 illustrate the obtained approximate results when $R = 1$

Table 1. The obtained values using IM.

Iterations	V_{pv} -IM	I_{pv} -IM	P_{pv} -IM	ε -IM
1	0.942812862	0.942812862	0.888896093	0.020389728
2	0.922004414	0.922004414	0.85009214	0.00041872
3	0.912933605	0.912933605	0.833447766	0.00948953
4	0.91658633	0.91658633	0.840130499	0.005836805
5	0.921613448	0.921613448	0.849371348	0.000809686
6	0.922412182	0.922412182	0.850844233	1.09529E-05
7	0.922423133	0.922423133	0.850864436	1.91849E-09
8	0.922423135	0.922423135	0.850864439	0.000000000
9	0.922423135	0.922423135	0.850864439	0.000000000




Figure 2. Voltage, current and power of solar cell with the absolute error values.

Table 2 and Figure 3 Illustrate the obtained approximate results when $R = 2$.

Table 2. The obtained values using IM

Iterations	V_{pv} -IM	I_{pv} -IM	P_{pv} -IM	ϵ -IM
1	0.942039802	0.471019901	0.443719494	0.025004419
2	0.919767328	0.459883664	0.422985969	0.002731946
3	0.908172101	0.45408605	0.412388282	0.008863282
4	0.909981837	0.454990918	0.414033472	0.007053546
5	0.915681905	0.457840953	0.419236676	0.001353477
6	0.917003597	0.458501799	0.420447799	3.1785E-05
7	0.917035366	0.458517683	0.420476931	1.62789E-08
8	0.917035382	0.458517691	0.420476946	4.44089E-15
9	0.917035382	0.458517691	0.420476946	0.000000000




Figure 3. Voltage, current and power of solar cell with the absolute error values.

Table 3 and Figure 5 Illustrate the obtained approximate results when $R = 3$.

Table 3. The obtained values using IM.

Iterations	V_{pv} -IM	I_{pv} -IM	P_{pv} -IM	ϵ -IM
1	0.94126616	0.313755387	0.295327328	0.030862786
2	0.917476245	0.305825415	0.280587554	0.007072871
3	0.903018143	0.301006048	0.271813922	0.007385231
4	0.902074754	0.300691585	0.271246287	0.00832862
5	0.90809742	0.30269914	0.274880308	0.002305954
6	0.910304588	0.303434863	0.276218148	9.87862E-05
7	0.910403215	0.303467738	0.276278004	1.59376E-07
8	0.910403374	0.303467791	0.276278101	4.1267E-13
9	0.910403374	0.303467791	0.276278101	0.000000000




Figure 4. Voltage, current and power of solar cell with the absolute error values.

Table 4 and Figure 6 illustrate the obtained approximate results when $R = 4$.

Table 4. The obtained values using IM.

Iterations	V_{pv} -IM	I_{pv} -IM	P_{pv} -IM	ϵ -IM
1	0.940491937	0.235122984	0.221131271	0.038751335
2	0.9151298	0.22878245	0.209365638	0.013389198
3	0.897428152	0.224357038	0.201344322	0.00431245
4	0.89244529	0.223111323	0.199114649	0.009295312
5	0.897748102	0.224437025	0.201487914	0.0039925
6	0.901401786	0.225350447	0.203131295	0.000338816
7	0.90173867	0.225434667	0.203283157	1.93238E-06
8	0.901740602	0.22543515	0.203284028	6.17006E-11
9	0.901740602	0.22543515	0.203284028	0.000000000




Figure 5. Voltage, current and power of solar cell with the absolute error values.

Table 5 and Figure 6 illustrate the obtained approximate results when $R = 5$.

Table 5. The obtained values using IM.

Iterations	V_{pv-IM}	I_{pv-IM}	P_{pv-IM}	$\epsilon-IM$
1	0.939717132	0.187943426	0.176613658	0.050624417
2	0.912726587	0.182545317	0.166613965	0.023633872
3	0.891352644	0.178270529	0.158901907	0.002259929
4	0.88049295	0.17609859	0.155053567	0.008599764
5	0.882268872	0.176453774	0.155679672	0.006823843
6	0.887741339	0.177548268	0.157616937	0.001351375
7	0.889058854	0.177811771	0.158085129	3.38608E-05
8	0.889092695	0.177818539	0.158097164	1.96857E-08
9	0.889092715	0.177818543	0.158097171	0.000000000
10	0.889092715	0.177818543	0.158097171	0.000000000




Figure 6. Voltage, current and power of solar cell with the absolute error values.

The obtained solution plot in the (no. of iterations)- ε -plane and the initial-output values prove that the proposed method IM have nine iterations indicated a fast behaviour. Parallel to this feature, it is noticed that the proposed method IM has a behaviour of the solution in the initial value x_0 with small error tolerance. Results from Tables 1-5 are showing that the suggested method IM exhibits low absolute errors after computed iterations which in turn demonstrating its efficiency.

5. Conclusions

This paper presents a new method to calculate the electrical parameter of the solar cell using implicit method. Values acquired from the proposed method IM were found to be sufficient and values for single diode solar cell were determined with fast convergence, more capable to determine these parameters towards establishing the final values.

6. References

- [1] Shihab SN and Sarhan MA 2014 Convergence analysis of shifted fourth kind Chebyshev wavelets, *IOSR J. Math.* **10** 2 54-58.
- [2] Al-Rawi SN and Al-Rubaie HR 2010 An Approximate solution of some continuous time Linear-Quadratic optimal control problem via Generalized Laguerre Polynomial *J Pure Appl. Sci.* **22** 1 85-97.
- [3] S. N. Al-Rawi, NUMERICAL SOLUTION OF INTEGRAL EQUATIONS USING TAYLOR SERIES, *Journal of the College of Education*, 5 (1992) 51-60.
- [4] Eleiwy JA and Shihab SN 2009 Chebyshev Polynomials and Spectral Method for Optimal Control Problem *Eng. Technol. J.* **27** 14 2642-2652.
- [5] SHIHAB SN and Sarhan MA 2014 New Operational Matrices of Shifted Fourth Chebyshev wavelets *Elixir Int. J.-Appl. Math.* **69** 1 23239-23244.
- [6] Al-Rawi SN, Al-Heety FA and Hasan SS 2010 A New Computational Method for Optimal Control Problem with B-spline Polynomials, *Eng. Technol. J.* **28** 18 5711-5718.
- [7] Delphi M and SHIHAB S 2019 Operational Matrix Basic Spline Wavelets of Derivative for linear Optimal Control Problem *Electron. Sci. Technol. Appl.* **6** 2 18-24.
- [8] Rasheed MS 2012 Study of the effects of acidic solutions on the physical properties of polymeric materials superimposed *Al-Mustansiriyah J. Sci.* **13** 49 6.
- [9] Rasheed MS and Shihab S 2020 Modelling and Parameter Extraction of PV Cell Using Single-Diode Model *Adv. Energy Conv. Mat.* **1** 2 96-104.
- [10] Rasheed MS and Shihab S 2020 Analysis of Mathematical Modeling of PV Cell with Numerical Algorithm *Adv. Energy Conv. Mat.* **1** 2 70-79.
- [11] Rasheed MS 2010 Approximate Solutions of Barker Equation in Parabolic Orbits *Eng. Technol. J.* **28** 3 492-499.
- [12] Rasheed MS 2010 An Improved Algorithm For The Solution of Kepler's Equation For An Elliptical Orbit, *Eng. Technol. J.* **28** 7 1316-1320.
- [13] Rasheed MS 2012 Acceleration of Predictor Corrector Halley Method in Astrophysics Application *Int. J. Emerg. Technol. Comput. Appl. Sci.* **1** 2 91-94.
- [14] Rasheed MS 2012 Fast Procedure for Solving Two-Body Problem in Celestial Mechanics *Int. J. Eng. Business Enterpr. Appl.* **1** 2 60-63.
- [15] Rasheed MS 2013 Solve the Position to Time Equation for an Object Travelling on a Parabolic Orbit in Celestial Mechanics, *Diyala J.Pure Sci.* **9** 4 31-38.
- [16] Rasheed MS 2013 Comparison of Starting Values for Implicit Iterative Solutions to Hyperbolic Orbits Equation *Int. J. Software Web Sci. (IJSWS)* **1** 2 65-71.
- [17] Rasheed MS 2014 On Solving Hyperbolic Trajectory Using New Predictor-Corrector Quadrature Algorithms *Baghdad Sci. J.* **11** 1 186-192.
- [18] Rasheed MS 2020 Modification of Three Order Methods for Solving Satellite Orbital Equation in Elliptical Motion *J. Univ. Anbar Pure Sci.* **14** 1 33-37.

- [19] Rasheed M and Barillé R 2017 Room temperature deposition of ZnO and Al: ZnO ultrathin films on glass and PET substrates by DC sputtering technique, *Opt. Quantum Electron.* **49** 5 1-14.
- [20] Rasheed M and Barillé R 2017 Optical constants of DC sputtering derived ITO, TiO₂ and TiO₂: Nb thin films characterized by spectrophotometry and spectroscopic ellipsometry for optoelectronic devices *J. Non-Crystall. Solids* **476** 1-14.
- [21] Rasheed M and Barillé R 2017 Comparison the optical properties for Bi₂O₃ and NiO ultrathin films deposited on different substrates by DC sputtering technique for transparent electronics *J. Alloys Comp.* **728** 1186-1198.
- [22] Saidani T, Zaabat M, Aida MS, Barille R, Rasheed M and Almohamed Y 2017 Influence of precursor source on sol-gel deposited ZnO thin films properties *J. Mat. Sci. Mat. Electron.* **28** 13 9252-9257.
- [23] Guergouria K, Boumezoued A, Barille R, Rechemc D, Rasheed M and Zaabata M 2019 ZnO nanopowders doped with bismuth oxide, from synthesis to electrical application *J. Alloys Comp.* **791** 550-558.
- [24] Bouras D, Mecif A, Barillé R, Harabi A, Rasheed M, Mahdjoub A and Zaabat M 2018 Cu: ZnO deposited on porous ceramic substrates by a simple thermal method for photocatalytic application *Ceramics Int.* **44** 17 21546-21555.
- [25] Saidi W, Hfaïdh N, Rasheed M, Girtan M, Megriche A and EL Maaoui M 2016 Effect of B₂O₃ addition on optical and structural properties of TiO₂ as a new blocking layer for multiple dye sensitive solar cell application (DSSC) *RSC Adv.* **6** 73 68819-68826.
- [26] AUKŠTUOLIS A, Girtan M, Mousdis GA, Mallet R, Socol M, Rasheed M and Stanculescu A 2017 Measurement of charge carrier mobility in perovskite nanowire films by photo-CELIV method *Proc. Romanian Acad. Ser. a-Math. Phys. Techn. Sci. Inform. Sci.* **18** 1 34-41.
- [27] Sultan OA, Hassoon KI and Rasheed MS 2003 Deterioration of Silicon Solar Cell Parameter with Ambient Temperature *Al-Mustansiriyah J. Sci.* **14** 1 25-31.
- [28] Tahir FS, Rasheed MS and Hameed IA 2012 Analysis the Performance of Silicon Solar Cell Parameters with the Ambient Temperature using Fuzzy Logic *J. Coll. Basic Educ.* **18** 75 173-183.
- [29] Tahir FS and Rasheed MS 2012 Decline in the Performance of Silicon Solar Cell Parameters with the Ambient Temperature in Baghdad *J. Coll. Basic Educ.* **18** 75 95-111.
- [30] Dkhilalli F, Megdiche S, Guidara K, Rasheed M, Barillé R and Megdiche M 2018 AC conductivity evolution in bulk and grain boundary response of sodium tungstate Na₂WO₄ *Ironics* **24** 1 169-180.
- [31] Dkhilalli F, Borchani SM, Rasheed M, Barille R, Guidara K and Megdiche M 2018 Structural, dielectric, and optical properties of the zinc tungstate ZnWO₄ compound *J. Mat. Sci. Mat. Electron.* **29** 8 6297-6307.
- [32] Dkhilalli F, Borchani SM, Rasheed M, Barille R, Shihab S, Guidara K and Megdiche M 2018 Characterizations and morphology of sodium tungstate particles *Royal Soc. Open Sci.* **5** 8 1-12.
- [33] Enneffati M, Louati B, Guidara K, Rasheed M and Barillé R 2018 Crystal structure characterization and AC electrical conduction behavior of sodium cadmium orthophosphate *J. Mat. Sci. Mat. Electron.* **29** 1 171-179.
- [34] Kadri E, Krichen M, Mohammed R, Zouari A and Khirouni K 2016 Electrical transport mechanisms in amorphous silicon/crystalline silicon germanium heterojunction solar cell: impact of passivation layer in conversion efficiency *Opt. Quantum Electron.* **48** 12 1-15.
- [35] Kadri E, Messaoudi O, Krichen M, Dhahri K, Rasheed M, Dhahri E, Zouari A, Khirouni K and Barillé R 2017 Optical and electrical properties of SiGe/Si solar cell heterostructures: Ellipsometric study *J. Alloys Comp.* **721** 779-783.
- [36] Kadri E, Dhahri K, Zaafouri A, Krichen M, Rasheed M, Khirouni K and Barillé R 2017 Ac conductivity and dielectric behavior of a-Si:H/c-Si_{1-y}Ge_y/p-Si thin films synthesized by molecular beam epitaxial method *J. Alloys Comp.* **705** 708-713.

- [37] Azaza NB, Elleuch S, Rasheed M, Gindre D, Abid S, Barille R, Abid Y and Ammar H 2019 3-(p-nitrophenyl) Coumarin derivatives: Synthesis, linear and nonlinear optical properties *Opt. Mat.* **96** 109328.
- [38] Enneffati M, Rasheed M, Louati B, Guidara K and Barillé R 2019 Morphology, UV–visible and ellipsometric studies of sodium lithium orthovanadate, *Opt. Quantum Electron.* **51** 9 299.
- [39] RASHEED M and Sarhan MA 2019 Solve and Implement the main Equations of Photovoltaic Cell Parameters Using Visual Studio Program *Insight-Math.* **1** 1.
- [40] Rasheed M and Sarhan MA 2019 Characteristics of Solar Cell Outdoor Measurements Using Fuzzy Logic Method *Insight-Math.* **1** 1.
- [41] RASHEED M and Sarhan MA 2019 Measuring the Solar Cell Parameters Using Fuzzy Set Technique *Insight-Electron.* **1** 1.
- [42] RASHEED M 2019 Linear Programming for Solving Solar Cell Parameters *Insight-Electron.* **1** 1.
- [43] RASHEED M 2019 Investigation of Solar Cell Factors using Fuzzy Set Technique *Insight-Electron.* **1** 1.
- [44] Jalal R, Shihab S, Abed Alhadi M, Rasheed M 2020 Spectral Numerical Algorithm for Solving Optimal Control Using Boubaker-Turki Operational Matrices, *Journal of Physics: Conference Series*, **1660** 1 012090.
- [45] RASHEED M and SHIHAB S 2019 Analytical Modeling of Solar Cells, *Insight Electron.* **1** 1.
- [46] RASHEED M and SHIHAB S 2019 Modeling and Simulation of Solar Cell Mathematical Model Parameters Determination Based on Different Methods *Insight Math.* **1** 1.
- [47] RASHEED M and SHIHAB S 2019 Parameters Estimation for Mathematical Model of Solar Cell, *Electron. Sci. Technol. Appl.*
- [48] SHIHAB S and RASHEED A 2019 Explicit Model of Solar Cells to Determine Voltages, *Insight Electron.*
- [49] RASHEED M and SHIHAB S 2019 Parameters Estimation of Photovoltaic Model Using Nonlinear Algorithms *Insight Electron.*
- [50] SHIHAB S and RASHEED M 2019 Modifications to Accelerate the Iterative Algorithm for the Single Diode Model of PV Model, *Insight Electron.*
- [51] Rasheed M and Shihab S 2020 Numerical Techniques for Solving Parameters of Solar Cell, *Appl. Phys.* **3** 2 16-27.
- [52] Abbas MM and Rasheed M 2020 Solid State Reaction Synthesis and Characterization of Aluminum Doped Titanium Dioxide Nanomaterials *J. Southwest Jiaotong Univ.* **55** 2 (2020) 1-10.
- [53] Aziz SH, Rasheed M and Shihab S 2020 New Properties of Modified Second Kind Chebyshev Polynomials *J. Southwest Jiaotong Univ.* **55** 3.
- [54] Sarhan MA, Shihab S and Rasheed M 2020 On the Properties of Two-Dimensional Normalized Boubaker Polynomials *J. Southwest Jiaotong Univ.* **55** 3.
- [55] Sarhan MA, Shihab S and Rasheed M 2020 A New Boubaker Wavelets Operational Matrix of Integration *J. Southwest Jiaotong Univ.* **55** 2.